



NOTE: ALLOW 15mm MORE
IN CUTOUT TO ACCOMMODATE
CORNER WELDS

NOTE: ALLOW 15mm MORE
IN CUTOUT TO ACCOMMODATE
CORNER WELDS

DRAIN CONNECTION

BSPF-NOMINATE

LEFT - CENT - RIGHT

CLIENT:			
APPLICATION:			
AIR FLOW (l/sec):		AIR VELOCITY (m/sec):	
PRESSURE DROP (Pa):		TOTAL FACE AREA (m ²):	
FRAME COLOUR:	WHITE	BLACK	PROFILE SPACING:
LOCATION QTY:	PORT	STRB	FWD AFT
TOTAL QTY REQUIRED:			
DATE REQUIRED:			
COMPLETED BY:		DATE:	

STEVE

MATERIALS:
BLADES: BLACK PPTV (TALCUM RE-INFORCED POLYPROPYLENE)
CASING: BLACK HDPE (HI-DENSITY POLYPROPYLENE - NOT UV STABILISED)
WHITE PVC - UV STABILISED

REAR SUMP DRAINING MOISTURE ELIMINATOR

STANDARD TEMPLATE

MODEL No: BME180 _____

 **Barclay
Engineering**

12-16 CATALANO RD - CANNING VALE WA 6155

TEL: (618) 9456 0300 FAX: (618) 9456 0388

EMAIL: info@barclayeng.com.au

WEB: www.barclayeng.com.au

FILE NAME: data\...\BME-RSD-HOR